



POWERING PROGRESS™

GATES CONCRETE HOSE

For High Pressure Placement of
Concrete at Casting Site



- > Durable
- > Flexible
- > Safe
- > Light Weight

Gates Concrete hose is an ideal hose for concrete pumps for Concrete supply at construction sites – delivery by concrete pumping machines with an abrasion resistant lining, abrasion resistant cover, high burst pressure, high flexibility, securely factory fitted couplings and being light weight.

> **High Abrasion Resistant Tube, Volume loss when tested to ISO 4649 (DIN 53516) 50 mm³ max.**



DESCRIPTION

CONCRETE HOSE	Nominal I.D.		Nominal O.D.		Working Pressure		Minimum Burst Pressure		Minimum Bend Radius	
	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm
	3	75	3.9	99	1233	85	2466	170	18	450
	4	102	5.3	128	1233	85	2466	170	24	612
	5	127	6.1	155	1233	85	2466	170	30	762
	6	152	7.2	184	1233	85	2466	170	36	912

CONSTRUCTION

- > **Tube** : NR/BR, black, smooth
- > **Reinforcement** : high tensile steel cord
- > **Cover** : NR/BR, black, smooth with cloth impression



GATES INDIA PVT. LTD.

Ambala Chandigarh Highway,
Lalru - 140 501 (Punjab)
Customer Care: 01762 506888/89
Fax: 01762 506833
Email: customercare@gatesind.com

SALES & SERVICE

Ahmedabad	9723453421
Bengaluru	9972126211
Faridabad	9811006873
Hyderabad	9963011126
Jaipur	9799812767
Kolkata	9874084691
Pune	9595745476

